

KYNAR® 50 HDCP 900

Kynar® resins are fluorinated homopolymers.

Kynar® 50 HDCP 900 is a thermoplastic fluorinated polymer resin. This product has been designed for Oil & Gas applications.

MAIN CHARACTERISTICS

RHEOLOGICAL PROPERTIES	VALUE	UNIT	TEST STANDARD
Melt Volume-Flow Rate	8	cm ³ /10min	ISO 1133
Temperature	250	°C	-
Load	10	kg	-

PROCESSING

Profile Extrusion, Sheet Extrusion, Other Extrusion

DELIVERY FORM

Pellets

ADDITIVES

Plasticizer

Arkema France - A French "société anonyme", registered in the Nanterre (France) Trade and Companies Register under the number 319 632 790
SIC/11-2018

Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/en/products/product-safety/disclaimer/index.html>

Kynar® is a registered trademark of Arkema
© 2022 Arkema Inc. All rights reserved.

kynar.com

Arkema Inc. – Technical Polymers
900 First Avenue
King of Prussia, PA 19406
Tel.: +1 610 205 7000
Fax: +1 610 205 7497
arkema-america.com

KYNAR®
BY ARKEMA

Headquarters: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
Tel.: +33 1 49 00 80 80
Fax: +33 1 49 00 83 96
arkema.com