

KYNAR® HSV 1800

Kynar® HSV1800 is a commercial functional homopolymer of vinylidene fluoride, specifically designed to be used as a cathode binder in Lithium Ion Batteries.

Main Characteristics:

- High adhesion
- Excellent cathode slurry stability with Nickel Manganese Cobalt Active Materials
- High molecular weight
- Functional

MAIN CHARACTERISTICS

PROPERTIES	VALUE	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Viscosity, 230°C, 100 s-1	80 - 85	kPoise	ASTM D3835
THERMAL PROPERTIES			
Melting Point, 73 °F	161 - 167	°C	ASTM D3418
OTHER PROPERTIES			
Density	1780	kg/m ³	ISO 1183
Specific Gravity, 73 °F	≥ 1.78	-	ASTM D792
POWDER PROPERTIES			
Appearance	White spheroidal powder	-	Visual

MAIN APPLICATIONS:

- Battery

[Slurry preparation](#)

PROCESSING

Coating, Casting

DELIVERY FORM

Powder

REGIONAL AVAILABILITY

North America, Europe, Asia Pacific, South and Central America, Near East/Africa

Arkema France - A French "société anonyme", registered in the Nanterre (France) Trade and Companies Register under the number 319 632 790 S00711-2018

Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/en/products/product-safety/disclaimer/index.html>

Kynar® is a registered trademark of Arkema
© 2022 Arkema Inc. All rights reserved.

kynar.com

KYNAR®
BY ARKEMA

Arkema Inc. – Technical Polymers
900 First Avenue
King of Prussia, PA 19406
Tel.: +1 610 205 7000
Fax: +1 610 205 7497
arkema-americas.com

Headquarters: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
Tel.: +33 1 49 00 80 80
Fax: +33 1 49 00 83 96
arkema.com