

【Inquiries】

AsahiKASEI Engineering Plastics Information Comprehensive Site

URL : <https://www.asahi-kasei-plastics.com/en/contact/>

AsahiKASEI



LEONA™ 91G55

Asahi Kasei Corporation - Polyamide 66/6I Copolymer

Tuesday, March 19, 2024

General Information

General

Material Status	• Commercial: Active	
Availability	• Africa & Middle East • Asia Pacific	• Europe • North America
Filler / Reinforcement	• Glass Fiber\Mineral, 55% Filler by Weight	
Features AKEP website	• Flow, High	• Good appearance
Uses	• Automotive Applications • Automotive Exterior Parts	• Industrial Applications • Windows & Doors
Part Marking Code (ISO11469) (ISO 11469)	• >PA66/6I-(GF+MD)55<	

Other Documentation

- Literature
- [Molding Conditions](#)
 - [SDS](#)
 - [Technical Handbook](#)

ASTM & ISO Properties ¹

Physical	Dry	Conditioned	Unit	Test Method
Density / Specific Gravity	1.68	--	g/cm ³	ASTM D792 ISO 1183
Molding Shrinkage				Internal Method
Across Flow	1.0	--	%	
Flow	0.20	--	%	
Mechanical	Dry	Conditioned	Unit	Test Method
Tensile Modulus (23°C)	15000	14000	MPa	ISO 527-1
Tensile Stress				
Break, 23°C	180	150	MPa	ISO 527-2
--	191	159	MPa	ASTM D638
Tensile Elongation				
Break	4.0	6.0	%	ASTM D638
Break, 23°C	3.0	4.0	%	ISO 527-2
Flexural Modulus				
--	13900	11900	MPa	ASTM D790
23°C	14000	12000	MPa	ISO 178
Flexural Strength				
--	262	231	MPa	ASTM D790
23°C	250	220	MPa	ISO 178

Disclaimer:

- Data shown are typical values obtained by proper testing methods and should not be used for specification purpose. Please use these data for selecting the most appropriate grade suitable for specific usage.

These data may be changed because of improvement in properties.

- Be sure to read the relevant SDS before handling and use, and always follow the Important Precautions.

- Do not use plastics in any of the following orally- or medically-related applications.

- Orally-related applications: any part, device or component which may come into direct oral contact or into direct contact with drinking foods or beverages.

For drinking water application, please consult Asahi Kasei Corporation.

- Medically-related applications: any part, device or component which may be used intracorporeally or which may in dialysis or other processes come into direct or indirect contact with body tissue, body fluids or transfusion fluids.

LEONA™ 91G55

Asahi Kasei Corporation - Polyamide 66/6I Copolymer

Impact	Dry	Conditioned	Unit	Test Method
Charpy Notched Impact Strength	5.0	6.0	kJ/m ²	ISO 179
Notched Izod Impact	54	63	J/m	ASTM D256
Hardness	Dry	Conditioned	Unit	Test Method
Rockwell Hardness				ASTM D785 ISO 2039-2
M-Scale	102	--		
R-Scale	120	--		
Thermal	Dry	Conditioned	Unit	Test Method
Deflection Temperature Under Load				ISO 75-2/A
1.8 MPa, Unannealed	220	--	°C	

Processing Information

Injection	Dry	Unit
Drying Temperature - Vacuum Dryer	80 to 90	°C
Drying Time - Vacuum Dryer	2.0 to 3.0	hr
Processing (Melt) Temp	275 to 295	°C
Mold Temperature	85 to 95	°C

Notes

¹ Typical properties: these are not to be construed as specifications.

Disclaimer:

- Data shown are typical values obtained by proper testing methods and should not be used for specification purpose. Please use these data for selecting the most appropriate grade suitable for specific usage.

These data may be changed because of improvement in properties.

- Be sure to read the relevant SDS before handling and use, and always follow the Important Precautions.

- Do not use plastics in any of the following orally- or medically-related applications.

- Orally-related applications: any part, device or component which may come into direct oral contact or into direct contact with drinking foods or beverages.

For drinking water application, please consult Asahi Kasei Corporation.

- Medically-related applications: any part, device or component which may be used intracorporeally or which may in dialysis or other processes come into direct or indirect contact with body tissue, body fluids or transfusion fluids.