


Datasheet

26/12/2018

Linear Low Density Polyethylene LL5405S
Description:

LL5405S is a Linear Low Density Polyethylene (LLDPE) developed for blown film extrusion. Films obtained with this product show a good processing performance balanced with good mechanical properties as well as processability. Very low gel amount.

Aditivação:

Slip, Antiblocking.

Applications:

Film, Blends with HDPE, Bags

Control Properties:

Feature	Method	Units	Values
Melt Flow Rate (190°C/2.16kg)	D 1238	g/10 min	1.0
Density	D 792	g/cm ³	0.919

Typical Properties - Films:

Blown Film Properties^a

Feature	Method	Units	Values
Tensile Strength at Break (MD/TD)	D 882	MPa	35/25
Elongation at Break (MD/TD)	D 882	%	1000/1200
Tensile Modulus - 1% Secant (MD/TD)	D 882	MPa	160/180
Dart Drop Impact	D 1709	g/F50	120
Elmendorf Tear Strength (MD/TD)	D 1922	gF	90/900
Haze	D 1003	%	18
Gloss - Angle 45°	D 2457	%	55
Gloss - Angle 60°	D 2457	%	80
COF internal 72h	D 1894	-	0.10
Blocking Load	D 1894	gf/100cm ²	8

(a) Film with 40 microns produce in a 40mm extruder and a blow-up ratio of 2.2:1. (MD = extrusion direction and TD = transversal direction).

Final Remarks:

1. The information presented in this Data Sheet reflects typical values obtained in our laboratories, but should not be considered as absolute or as warranted values. Only the properties and values mentioned on the Certificate of Quality are considered as guarantee of the product.
2. For regulatory information of the product, please refer to Regulatory Document or contact our Technical Assistance Area.
3. For information about safety, handling, individual protection, first aids and waste disposal, please refer to MSDS.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.