


Datasheet

26/12/2018

Linear Low Density Polyethylene FLEXUS 7200XP
Description:

Braskem FLEXUS 7200XP is a Linear Low Density Polyethylene produced through metallocene catalyst with hexene copolymer. The resin have excellent mechanical properties and differentiated performance in optical properties.

Applications:

Stretch Films

Processes:

Cast film extrusion

Control Properties:

Feature	Method	Units	Values
Melt Flow Rate (190°C/2.16kg)	D 1238	g/10 min	3.5
Density	D 792	g/cm ³	0.918

Typical Properties - Films:

Blown Film Properties

Feature	Method	Units	Values
Highlight - Ultimate Test (1)(2)	D 4649	%	380
Highlight - Puncture (1)(2)	D 4649	kg	3.2
Highlight - Retention Maximum Force (1)(2)	D 4649	kg	3.5
Highlight - Retention Ending Force (1)(2)	D 4649	kg	2.5
Highlight - Retention Loss (1)(2)	D 4649	%	39
Highlight - Cling (1)(2)	D 4649	g	16
Highlight - Unwind Force (1)(2)	D 4649	kgf	4.8
Highlight - Sond level (1)(2)	D 4649	dB	76
Highlight - Elongation Force (1)(2)	D 4649	kgf	37
Haze	D 882	%	2
Brightness	D 882	%	94
Gloss - Angle 45°	D 2457	%	98

(1) 23µm thickness film, processed in a 3 layer coextruder (2) Highlight tested at 300%

Final Remarks:

- The information presented in this Data Sheet reflects typical values obtained in our laboratories, but should not be considered as absolute or as warranted values. Only the properties and values mentioned on the Certificate of Quality are considered as guarantee of the product.
- For regulatory information of the product, please refer to Regulatory Document or contact our Technical Assistance Area.
- For information about safety, handling, individual protection, first aids and waste disposal, please refer to MSDS.
- The mentioned values in this report can be changed at any moment without Braskem previous communication.