

[TOP](#)

POLYETHYLENE

Products of Daelim are NO. 1 in quality and service

» [HOME](#) > [Product&Service](#) > Polyethylene



DAELIM POLYETHYLENE

High-quality synthetic resin, DAELIM POLY HDPE is being manufactured in the world class Yeosu Complex equipped with state-of-the-art facilities



 **Daelimpoly**

 **Print**

 **LIST**

6007LD

Customer Benefits

Excellent Processability
High Anti-static Property
Excellent Stiffness

Suggested Applications

Small Bottles
[Milk, Fruit Juice Bottles]

Processing Recommendation

Stock Temp. : 170~ 190℃

Specification Data

ASTM D 1248-Type IV, Class A, Category 4
FDA Regulation 177. 1520 Suitable for Food Packaging

Properties	Test Method	Unit	Value
Melt Index (190℃, 2.16Kg)	ASTM D 1238	g/10min	0.65
Density	ASTM D 1505	g/cm ³	0.962
Tensile Yield Strength	ASTM D 638	kg/cm ²	320
Ultimate Elongation	ASTM D 638	%	>600
Flexural Modulus	ASTM D 790	kg/cm ²	14,000
IZOD Impact Strength (23℃)	ASTM D 256	kg.cm/cm	5
Brittleness Temperature	ASTM D 746	℃	<-76
ESCR (Condition B, F50)	ASTM D 1693	Hr	20

[+ | Go Family Site](#)

101 The Korea Chamber of Commerce & Industry B/D, 45 4ga Namdaemunro, Jung-gu, Seoul, 100-743 Korea **DAELIM Petrochemical Division** (82)-2-3708-3000
COPYRIGHT © 2002-2005 ALL RIGHTS RESERVED BY DAELIM