

[TOP](#)

POLYETHYLENE

Products of Daelim are NO. 1 in quality and service

» [HOME](#) > [Product&Service](#) > Polyethylene



DAELIM POLYETHYLENE

High-quality synthetic resin, DAELIM POLY HDPE is being manufactured in the world class Yeosu Complex equipped with state-of-the-art facilities



 **Daelimpoly**

 **Print**

 **LIST**

LH-418BL

Customer Benefits

Hexene Comonomer
Outstanding Stress Cracking Resistance
Excellent Processabilities

Suggested Applications

Geo Sheet
Geo Membran

Processing Recommendation

Stock Temp. : 190~ 220℃

Specification Data

ASTM D 1248-Type III, Class A, Category 5

Properties	Test Method	Unit	Value
Melt Index (190℃, 2.16Kg)	ASTM D 1238	g/10min	0.23
Density	ASTM D 1505	g/cm ³	0.947
Tensile Yield Strength(at Yield, 50mm/min)	ASTM D 638	kg/cm ²	190
Ultimate Elongation	ASTM D 638	%	>600
Flexural Modulus	ASTM D 790	kg/cm ²	7,000
OIT(200℃, Al Pan)	ASTM D 3895	min	>120
Brittleness Temperature	ASTM D 746	℃	<-118
ESCR (Condition B, F0)	ASTM D 1693	hr	>2,000

[+ Go Family Site](#)

10# The Korea Chamber of Commerce & Industry B/D, 45 4ga Namdaemunro, Jung-gu, Seoul, 100-743 Korea **DAELIM Petrochemical Division** (82)-2-3708-3000
COPYRIGHT © 2002-2005 ALL RIGHTS RESERVED BY DAELIM