

**HELLENIC
PETROLEUM****HELLENIC PETROLEUM S.A.****Chemicals Marketing Division**17th km NATIONAL RD. ATHENS-KORINTHOS, GR-19300

ASPROPYRGOS, TEL.: +301 5539061, FAX: +301 5539060

ECOLEN[®] HZ40P

POLYPROPYLENE HOMOPOLYMER RESIN

Description		Applications		
ECOLEN [®] HZ40P is a polypropylene homopolymer, featuring:		Typical applications for this grade are:		
• good processability • excellent antigasfading properties.		• heavy denier staple fibres • continuous filaments and • decorative ribbons.		

Typical properties	Method	Unit	Value^[1]
Melt Flow Rate (230°C, 2.16Kg)	ASTM D 1238	g/10 min	12
Density	ASTM D 792	g/cm ³	0.9
Flexural modulus	ASTM D 790	MPa	1550
Tensile Strength at Yield	ASTM D 638	MPa	34
Elongation at yield	ASTM D 638	%	12
Izod Impact Strength (notched) at 23°C	ASTM D 256	J/m	30

[1] Indicated values are averages and are not to be considered as product specifications.

Product is available in: 25 Kgs bags, big bags and bulk.

ECOLEN[®] HZ40P is suitable for food contact.

Issued: February 2002