



Rigidex® HD6070FA

Product Technical Information

HDPE for Film products

Rigidex® HD6070FA is a high density polyethylene suitable for a range of high quality film applications.

Typical applications

- Cast or blown film as a blending partner to increase stiffness of LDPE or LLDPE
- Cast co-extrusion for high stiffness films or non blocking layers
- Extrusion coating as a blending partner or in co-extrusion with LDPE extrusion coating grades. With such blends (minimum content of LDPE of 20%), coated substances such as paper and cardboard can be used e.g. for photographic paper and for ream wrapping.

Benefits and Features

- High stiffness
- Very low gel level
- Easy extrudability
- Good optical properties in cast extrusion
- High gloss
- Better heat and scratch resistance compared to LDPE and lower blocking
- In extrusion coating : good processability, high coating speed, good draw down ability with reasonable neck-in, good adhesion on many substrates

Properties		Test Methods	Values	Units
Physical				
Density		ISO 1872	960	kg/m ³
Melt Flow Rate	2.16 kg load	ISO 1133	7.6	g/10min
Vicat softening tempertuare		ISO 306 Method A	127	°C
DSC melting temperature (10°C/min)		INEOS Method	132	°C
Thermal conductivity		ASTM C177	0.48	W/m ²
Specific heat		-	2300	J/kg °C
Additives:antioxidants				

February, 2008

Published by
INEOS Polyolefins



Rigidex® HD6070FA

Film*

Tensile Stress @ Break	MD/TD	ISO 1184	50	MPa
Elongation @ Break	MD/TD	ISO 1184	500	%
1% Secant modulus	MD/TD	ISO 1184	700	MPa
Haze		ASTM D1003	7	%
Gloss (45°)		ASTM D2457	75	%

- Data should not be used for specification work.

* 15 µm cast film extruded at 200°C – MD: machine direction - TD: transverse direction

Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, send an email to psnohreg@innovene.com. Unless specifically indicated, the products mentioned herein are not suitable for applications in the medical or pharmaceutical sector.

Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained from the website www.ineospolyolefins.com. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

Exclusion of Liability

Although INEOS POLYOLEFINS endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS POLYOLEFINS is accurate and up to date, no representation or warranty, express or implied is made by INEOS POLYOLEFINS as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS POLYOLEFINS are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS POLYOLEFINS materials are suitable for the particular purpose intended and INEOS POLYOLEFINS shall not be responsible for any loss or damage caused by misuse of INEOS POLYOLEFINS products. To the maximum extent permitted by law, INEOS POLYOLEFINS accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS POLYOLEFINS materials or the use of INEOS POLYOLEFINS materials in conjunction with such other materials.

February, 2008

Published by
INEOS Polyolefins