



V1160

High Density Polyethylene (HDPE)

Description:

V1160 is a High Density Polyethylene resin for injection molding with high flow ability. It is suitable for household, toy. It also meets the F.D.A. requirement in the code of federal regulations in 21 CFR 177.1520 for food contact.

Physical Properties:	Method	Unit	Value
Melt Flow Index (2.16 kg/190°C)	ASTM D1238	g/10min.	15
Melt Flow Index (5 kg/190°C)	ASTM D1238	g/10min.	43
Density	ASTM D792	g/cm ³	0.957
Tensile Strength at Yield	ASTM D638	MPA	29
Tensile Strength at Break	ASTM D638	MPA	13.5
Ultimate Elongation	ASTM D638	%	130
Hardness Shore D	DIN 53505	-	65.5
Charpy Notched Impact Strength (at 23°C)	DIN 53453	mJ/mm ²	2.5
Vicat Softening Temperature	ASTM D1525	°C	125
Environmental Stress Cracking Resistance (condition B, F₅₀)	ASTM D1693	hours	3

Processing Technique

Processing Temperature : 170 – 250 °C

****However, the actual processing conditions depend on mold design, machine and other environments.****

Remark: The values presented on the above are typical laboratory average, not to be construed as specifications and may vary within moderate ranges. The applicability or the accuracy of this information or the suitable of our products cannot be guaranteed because the conditions of use on the part or our uses are beyond our control.

Product Data sheet



บริษัท ไออาร์พีซี จำกัด (มหาชน)

555/2 ถนนวิภาวดีรังสิต อาคาร บี ชั้น 6 ถนนวิภาวดีรังสิต แขวงจตุจักร เขตจตุจักร กรุงเทพฯ 10900 โทร. +66(0)2649-7000, 66(0)2649-7777 แฟกซ์: +66(0)2649-7002

IRPC Public Company Limited

555/2 Energy Complex Building B, 6th Floor, Vibhavadi Rangsit Road, Chatuchak, Bangkok 10900 THAILAND. TEL: +66(0)2649-7000, 66(0)2649-7777 FAX: +66(0)2649-7002 www.irpc.co.th, www.irpcmarket.com

REV. 20110601