

SolutionPartner


ABS XR418

Injection Molding Grade

Description

High Heat, Low emission

Application

Automotives Interior parts

Properties	Test Condition	Test Method	Unit	Typical Value
Physical				
Density		ISO 1183	g/cm ³	1.06
Molding Shrinkage (Flow), 3.2mm		ISO 294-4	%	0.4~0.7
Melt Flow Rate	220℃/10kg	ISO 1133	g/10min	6.0
Mechanical				
Tensile Strength @ Yield	50mm/min	ISO 527	MPa	48
Tensile Modulus	1mm/min	ISO 527	MPa	2,550
Flexural Strength	2mm/min	ISO 178	MPa	76
Flexural Modulus	2mm/min	ISO 178	MPa	2,650
IZOD Impact Strength, 80*10*4mm (Notched)	23℃	ISO 180/1A	kJ/m ²	14.0
	-30℃		kJ/m ²	-
Charpy Impact Strength, 80*10*4mm (Notched)	23℃	ISO179/1eA	kJ/m ²	13.0
	-30℃		kJ/m ²	-
Rockwell Hardness		ISO 2039	-	113
Thermal				
Heat Deflection Temp. 120*10*4mm (unannealed)	1.8MPa	ISO 75/Be	℃	90
	0.45MPa	ISO 75/Ae	℃	107
Vicat Softening Temperature	50N, 50℃/h	ISO 306	℃	108
CLTE, 23℃ to 60℃		ISO 11359-2	10 ⁻⁵ m/m℃	8.0~9.0
			10 ⁻⁵ m/m℃	8.0~9.0
Flammability		UL94		
Relative Temperature Index		UL 746B		
Electrical			℃	
Mechanical with Impact			℃	
Mechanical without Impact			℃	
Electrical				
Comparative Tracking Index(CTI)	Solution A	IEC 60112	Volts	
Surface Resistivity		IEC 60093	Ohm	
Volume Resistivity	23℃	IEC 60093	Ohm·m	
Electric Strength, 1mm	23℃	IEC 60243-1	kV/mm	

Note) Typical values are only for material selection purpose, and variation within normal tolerances are for various colors.

Values given should not be interpreted as specification and not be used for part or tool design.

All properties, except melt flow rate are measured on injection moulded specimens and after 48 hours storage at 23℃, 50% relative humidity.

Updated : 25-Apr-16

The information contained herein, including, but not limited to, data, statements and typical values, are given in good faith. LG Chem makes no warranty or guarantee, expressed or implied, (i) that the result described herein will be obtained under end - use conditions, or (ii) as to the effectiveness or safety of any design incorporating LG Chem materials, products, recommendations or advice. Further, any information contained herein shall not be construed as a part of legally binding offer. Especially, the typical values should be regarded as reference values only and not as binding minimum values. Each user bear full responsibility for making its own determination as to the suitability of LG Chem's materials, products, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating LG Chem material or products will be safe and suitable for use under end - use conditions. The data contained herein can be changed without notice as a result of the quality improvement of the products.

SolutionPartner


ABS XR418

Injection Molding Grade

Description

High Heat, Low emission

Application

Automotives Interior parts

Processing Guide (Injection Molding)

Processing Parameters		Unit	Value
Drying Temperature		°C	80 ~ 90
Drying Time		hrs	3 ~ 4
Recommendable Moisture Content		%	0.05 below
Melt Temperature		°C	230 ~ 270
Cylinder Temperature	Rear	°C	180 ~ 210
	Middle	°C	210 ~ 230
	Front	°C	230 ~ 240
Nozzle Temperature		°C	230 ~ 240
Mold Temperature		°C	40 ~ 60
Back Pressure		kg/cm ²	10 ~ 30
Measuring Speed		rpm	Low speed

Note) Back Pressure & Measuring Speed are only mentioned as general guidelines.

These may not apply or need adjustment in specific situations such as low shot sizes, thin wall molding and gas-assist molding.

Updated : 25-Apr-16

The information contained herein, including, but not limited to, data, statements and typical values, are given in good faith. LG Chem makes no warranty or guarantee, expressed or implied, (i) that the result described herein will be obtained under end - use conditions, or (ii) as to the effectiveness or safety of any design incorporating LG Chem materials, products, recommendations or advice. Further, any information contained herein shall not be construed as a part of legally binding offer. Especially, the typical values should be regarded as reference values only and not as binding minimum values. Each user bear full responsibility for making its own determination as to the suitability of LG Chem's materials, products, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating LG Chem material or products will be safe and suitable for use under end - use conditions. The data contained herein can be changed without notice as a result of the quality improvement of the products.