

DATASHEET

ASTM Property



Grade	UL914A
Product	LLDPE

General Information

Key Features	- For blown film, Melt blend product of LDPE and LLDPE - Good mechanical properties, Excellent optical properties, Good processability - Including slip agent, anti-blocking agent, processing aid
--------------	--

Applications	Lamination film
--------------	-----------------

Item	Measuring Method	Unit	Value
------	------------------	------	-------

Physical

Melt Flow Index	ASTM D1238	g/10min	1.5
-----------------	------------	---------	-----

Density	ASTM D1505	g/cm ³	0.920
---------	------------	-------------------	-------

Blown Film Properties (40 μm)

Ultimate Tensile Strength	MD	ASTM D882	kgf/cm ²	370
	TD			345

Ultimate Elongation	MD	ASTM D882	%	710
	TD			730

Elmendorf Tear Strength	MD	ASTM D1922	g/μm	3.6
	TD			7.7

Dart Impact Strength	ASTM D1709	g	100
----------------------	------------	---	-----

Haze	ASTM D1003	%	5
------	------------	---	---

Gross (45°)	ASTM D2457	%	85
-------------	------------	---	----

· Processing Condition : Φ50mm LLDPE Blown Film Extruder

Temperature 180°C, Die Gap 2.2mm, BUR 2.1, FLH 32cm

1. Physical Properties : these are not to be construed as specifications

2. ISO 9001, 14001, /TS 16949

* The last update date : 2021/10/01