



Home / Products & Technology / Polymers / **Dexflex E756-1 BLK**

Dexflex E756-1 BLK

Description

Dexflex E756-1 BLK is an unfilled PP TPO copolymer with excellent impact resistance.

Availability

North America

» CustomerXpress

» Find a Sales Contact

» Request Product Information

Legend

SDS - Safety Data Sheet

PSB - Product Stewardship Bulletin

Information

SDS

Safety Summary

Product Data and Technical Information

Typical Properties

Melt Flow Rate (230°C/2.16 kg)	0.5 g/10 min
Density (23°C)	0.90 g/cm ³
Tear Strength	100 kN/m
Tensile Stress at Yield	14 MPa
Mold Shrinkage	

Process

Injection Molding

Resin

Polypropylene Compounds

Applications

Interior Automotive Applications

Prohibited Applications of Compounded Polyolefins:

The use of LyondellBasell Compounded Polyolefins in the following applications is prohibited:

- All parts for Aeronautical use
- All parts for Train transportation use
- Air bag unit housings
- Seat belt systems and mechanisms
- Brake systems and mechanisms
- Pedals (brake, gas, clutch)
- Steering systems and mechanisms
- All parts with flammability requirements for Building and Constructions
- All parts with flammability requirements for Industrial applications use
- All parts for Medical applications use

This site uses cookies. By continuing to browse the site, you agree to our use of cookies.

» **ACCEPT**

[Privacy](#)