

[Home](#) / [Products & Technology](#) / [Polymers](#) / **Moplen EP341R**

Moplen EP341R

Description

Moplen EP341R is a high flow, high crystalline polypropylene impact copolymer resin, with good stiffness impact balance, excellent flowability and low warpage. Typical customer applications are electrical appliances, medium to large industrial containers, caps.

Availability

Africa-Middle East, Asia-Pacific, Australia and New Zealand

[» CustomerXpress](#)[» Find a Sales Contact](#)[» Request Product Information](#)

Legend

SDS - Safety Data Sheet

PSB - Product Stewardship Bulletin

[Information](#)[SDS](#)[PSB](#)

Product Data and Technical Information

Typical Properties

Melt Flow Rate (230°C/2.16 kg)	24 g/10 min
Density	0.90 g/cm ³
Flexural Modulus	1150 MPa
Tensile Strength at Yield	24 MPa
Tensile Elongation at Yield	6 %
Notched Izod Impact Strength (23°C)	60 J/m
Deflection Temperature Under Load	96 °C

Process

Injection Molding

Resin

Impact Copolymer Polypropylene

Applications

Appliances, Industrial Packaging

This site uses cookies. By continuing to browse the site, you agree to our use of cookies.

» **ACCEPT**

[Privacy](#)

