

[Home](#) / [Products & Technology](#) / [Polymers](#) / **Petrothene NA217000X07**

Petrothene NA217000X07

Description

Petrothene NA217000X07 is a high speed, lightweight coating resin selected by customers for use with paper, films and other base stocks. This resin can be extruded at line speeds of 1500 ft/min or higher. Products made from materials coated with NA217000X07 typically include flexible packaging, milk cartons, industrial papers and foil mounting, single-ply bags, pouch bags, cup stock, fiber drums, corrugated boxes and fiberboard containers.

Availability

North America

[» CustomerXpress](#)[» Find a Sales Contact](#)[» Request Product Information](#)

Legend

SDS - Safety Data Sheet

PSB - Product Stewardship Bulletin

[Information](#)[SDS](#)[Technical Literature](#)

Product Data and Technical Information

Typical Properties

Melt Flow Rate (190°C/2.16 kg)	5.6 g/10 min
Density (23°C)	0.923 g/cm ³

Process

Extrusion Coating

Resin

Low Density Polyethylene

Applications

Bags & Pouches, Colour Concentrates, Food Packaging Film, Lamination Film, Sealants

This site uses cookies. By continuing to browse the site, you agree to our use of cookies.

[» ACCEPT](#)[Privacy](#)