



Home / Products & Technology / Polymers / **Sequel 1719HF-UV WHIT**

# Sequel 1719HF-UV WHIT

## Description

*Sequel* 1719HF-UV WHIT medium high melt flow, high flexural modulus, UV-stabilized, mineral-filled thermoplastic elastomeric olefin (TEO) resin has an excellent balance of properties.

## Availability

North America

» CustomerXpress

» Find a Sales Contact

» Request Product Information

### Legend

SDS - Safety Data Sheet

PSB - Product Stewardship Bulletin

Information

SDS

PSB

Safety Summary

## Product Data and Technical Information

### Typical Properties

Melt Flow Rate (230°C/2.16 kg) **15 g/10 min**

Density (23°C) **1.10 g/cm<sup>3</sup>**

Flexural Modulus (23°C, 2mm/min) **1860 MPa**

Mold Shrinkage

## Process

Injection Molding

## Resin

Polypropylene Compounds

## Applications

Automotive Parts, Exterior Automotive Applications

### Prohibited Applications of Compounded Polyolefins:

The use of LyondellBasell Compounded Polyolefins in the following applications is prohibited:

- All parts for Aeronautical use

- All parts for Train transportation use
- Air bag unit housings
- Seat belt systems and mechanisms
- Brake systems and mechanisms
- Pedals (brake, gas, clutch)
- Steering systems and mechanisms
- All parts with flammability requirements for Building and Constructions
- All parts with flammability requirements for Industrial applications use
- All parts for Medical applications use

This site uses cookies. By continuing to browse the site, you agree to our use of cookies.

» ACCEPT

[Privacy](#)