



Data Sheet
Date Prepared:

HDPE MK910

YUCLAIR MK910 is a high-density polyethylene resin with high melt index of 20.0g/10min. It is particularly designed for conjugate fibers and shows excellent spinnability and color stability.

YUCLAIR MK910 complies with FDA regulation 21 CFR 177.1520.

Application / Use Case

Fiber / Bicomponent

Specification

	Specification	Unit	Test Method
Density	0.956	g/cm ³	ASTM D792
Melt Index	20	g/10min	ASTM D1238

Physical Properties

	Value	Unit	Test Method
Softening Point(Vicat)	121	°C	ASTM D1525
Tensile Strength at Yield	255	kg/cm ²	ASTM D638
IZOD Impact strength	6.0	kg cm/cm	ASTM D256

These are typical properties only, and are not to be construed as specific limits.

Head Office
99 Seorin-dong, Jongno-gu, Seoul 110-110, Korea
Tel. 82-2-2121-5114 Fax. 82-2-2121-7001
SK Institute of
Technology
140-1 Woncheon-dong, Yuseong-gu, Taejeon, Korea
Tel. 82-42-609-8270 Fax. 82-42-609-8680
Online
SK energy co., ltd. : www.SKenergy.com
Chemical Business : www.skchem.com

ISO 9001 Certified