



Technical Data Sheet

Europrene®
SEBS**SOL THX 1050**

Styrene - Ethylene/Butylene Radial Block Copolymer

Europrene® SOL THX 1050 is a multi-arm block copolymer obtained by selective hydrogenation of branched styrene-butadiene-styrene block copolymers. It contains a non-staining, TNPP free antioxidant system.

Main Properties	Test Method	Unit	Typical Value
Bound Styrene Content	Internal Method	% wt	7
Volatile Matter	ASTM D 5668	%	1 max
TP*	Internal Method	cSt	4,5
SSI*	Internal Method	%	12

*1% wt in Eni SN 150

Key Features

Europrene® SOL THX 1050 is a tailored amorphous polymer designed as a viscosity index improver for lubricating oil.

Main Applications

The product is used as oil viscosity modifier.

Physical Form

Europrene® SOL THX 1050 is produced in Ravenna Plant (Italy) in a compact form.

Packaging

Available in bags on pallet. For detailed information, please refer to your Versalis representative.

Storage Conditions

Store the preparation in a covered place in sealed packaging, away from sunlight and heat sources. Ensure the proper ventilation in all storage areas.

Shelf life: 24 months

Please consult the relevant safety data sheet for more detailed information.

The information and data presented herein are to the best of our knowledge true and accurate, but no warranty or guarantee, expressed or implied, is made nor is any liability accepted with respect to the use of such information and data.

® Registered Trademark

June 2023