

Extir®


versalis

CM Galileo Europa 5 AE

Technical data sheet

info.styrenics@versalis.eni.com

Flame retardant - Improved insulation - HBCD-free - Does not contain CFC and HCFC - Reduced pentane content

Extir® CM Galileo Europa 5 AE is an expandible light grey coloured polystyrene, with flame retardant properties. The beads have a very low dimensional dispersion and a reduced content of blowing agent. Extir® CM Galileo Europa 5AE contains an atherman additive which minimize heat conduction, giving excellent thermal insulation properties to the molded pieces. Extir® CM Galileo Europa 5 AE is HBCD-free and does not contain CFC or HCFC. The product is not suitable for food contact.

Applications

Thanks to its superior insulation properties, Extir CM Galileo Europa 5 AE can be used for:

- ETICS
- Roof insulation
- Floor insulation

Technical Informations

Beads size	mm	0,9-1,6
Bulk density	kg/m ³	590-630
Typical pentane content	%	<6
Minimum apparent density		
on a continuous pre-expander after one expansion	kg/m ³	18
on a continuous pre-expander after two expansions	kg/m ³	12
on a discontinuous pre-expander	kg/m ³	15
Usual density range	kg/m ³	12-25

For more information, please refer to the brochure "Extir® for building"

Processing

Extir® CM products can be processed in three steps.

- Pre-expansion** Extir® CM Galileo Europa 5 AE can be pre-expanded to the densities indicated above with continuous or discontinuous traditional pre-expanders. Lower densities can be achieved with double expansion.
- Aging** Beads' aging time could be between 10 and 48 hours. It may vary according to the desired density and climate conditions.
- Molding** Extir® CM Galileo Europa 5 AE can be molded in common block molds.

Finished products present great sintering, low shrinkage and good surface appearance.

Extir®

CM Galileo Europa 5 AE



versalis

Technical data sheet

info.styrenics@versalis.eni.com

Certifications

✓Euroclass E ✓LNE, on demand ✓B1 nach DIN4102, on demand

Extir® CM Galileo Europa 5 AE raw material are officially certified Euroclass E EN 13501-1, compliant with EN 13163 Annex E. For the products bearing French certification (LNE) or German certification (B1 nach DIN 4102), certificates are provided on request. The flame retardant properties of the finished product are effective only after blowing agent removal and after a proper aging time.

Storage



Keep the product in a dry well ventilated store between 15- 20°C.

For product packaged in octabins and stored correctly, the guaranteed shelf-life is one month from delivery.

The boards and molded parts made of Extir CM Galileo Europa 5AE must not be exposed to solar radiation or packed in transparent film. The use of an opaque or white film is strongly recommended

Safety

During the processing of Expandable Polystyrene, an explosive atmosphere could be created due to air / pentane mixtures. For this reason, all possible causes of ignition such as naked flames or sparks must be avoided, it is necessary to work in adequately ventilated places and a smoking should be forbidden. Adequate electrical grounding of machinery and of pneumatic conveyance lines is recommended. For further information relating to storage, packaging and processing precautions, please refer to the Technical Bulletin "Styrenics - Technical data sheets" and to the "Extir Safety Data Sheets".

All indicated data refer to natural grades. The data, information and suggestions are provided for guidance purposes only. The Company accepts no responsibility for the results obtained therefrom, as neither for their utilization in infringement of possible patent rights. However the Company will provide the guaranteed values for each product on demand.

*registered trademark

Emissione 11/2021

Extir[®]

CM Galileo Europa 5 AE



versalis

Technical data sheet
info.styrenics@versalis.eni.com