



Product information

VESTOLIT® S 6058

Polyvinyl chloride for thermoplastic processing

VESTOLIT S 6058 is a free-flowing suspension(S) PVC. This product is mainly used for the production of profiles and pipes as well as expanded profiles and sheets.

Application	rigid	flexible
Extrusion		
- Profiles, pipes	●	
- Films/foils, sheets	○	
- Expanded profiles, sheets	●	
Blow moulding		
- Bottles, containers		
Injection moulding		
- Injection mouldings	○	
Calendering		
-HT films		
● recommended ○ feasible ■ Additiv		

Property	Method	Unit	Value ¹⁾
K value	DIN EN ISO 1628-2	-	60
Apparent bulk density	DIN EN ISO 60	g/cm ³	0.58
Sieve analysis - retained on 0.063 mm sieve	DIN EN ISO 4610	%	≥ 90
Sieve analysis - retained on 0.200 mm sieve	DIN EN ISO 4610	%	≤ 20
Volatile content	DIN EN ISO 1269	%	≤ 0.3

1) The figures quoted above are typical values, and do not form part of the specification.

Version 09.2013

VESTOLIT GmbH • D 45753 Marl • P.O. Box 10 23 60
 Phone: + 49 23 65 / 49 - 05 • Fax: + 49 23 65 / 49 - 40 00 • E-Mail: info@vestolit.de

This information is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third part patent rights in particular, no guarantee of properties in the legal sense is implied. We reserve the right to make any change according to technical progress of further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Reference to trade names used by other companies neither recommendation, nor is intended to suggest that similar products could be used. All our business transactions shall exclusively be governed by our General sales Conditions. ® = registered trademark