



Phone: 1.610.459.1000
 Phone: 1.800.000.0000
 Fax: 610.459.1084
 490 West Lenni Road
 Lenni, PA 19052 U.S.A.
 Email: info@westlakeplastics.com

Propylux® VF



Propylux® VF is manufactured as a void-free polypropylene (PP) copolymer. Highly chemically resistant, all Propylux® VF sheet and rod products are 100% ultrasonically tested and guaranteed to be free of voids or porosity. Propylux® VF is suitable for a wide range of uses, from chemical storage tanks to machined pump housings and manifolds.


INDUSTRY



Chemical Process



Engineering



Semiconductor and
ESD

COLORS AVAILABLE



ATTRIBUTES



Chemical Resistance



Food Contact



SHAPES

Compression Sheet



Extruded Film





Phone: 1.610.459.1000
Phone: 1.800.000.0000
Fax: 610.459.1084
490 West Lenni Road
Lenni, PA 19052 U.S.A.
Email: info@westlakeplastics.com

Propylux® VF

TECHNICAL SPECIFICATIONS

PROPERTY	TEST STANDARD	ENGLISH UNITS	METRIC UNITS
Mechanical			
Flexural Modulus - 1% Secant	D790	143 kpsi	985 MPa
Tensile Elongation @ Break	D638	675 %	675 %
Tensile Elongation @ Yield	D638	13 %	13 %
Tensile Strength @ Break	D638	3.2 kpsi	22 MPa
Tensile Strength @ Yield	D638	4 kpsi	28 MPa
Thermal			
HDT @ 64 psi	D648	176 °F	80 °C
Other			
Specific Gravity	D792	0.90	0.90

SIZING



Phone: 1.610.459.1000
Phone: 1.800.000.0000
Fax: 610.459.1084
490 West Lenni Road
Lenni, PA 19052 U.S.A.
Email: info@westlakeplastics.com

Propylux® VF

Compression Sheet Sizing

48" Length by 24" Width

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	

96" Length by 48" Width

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	

120" Length by 48" Width

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	

120" Length by 60" Width

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.50" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)
3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)	

Film Sizing

26" Width

0.002" (0.05mm)	0.003" (0.08mm)	0.004" (0.1mm)	0.005" (0.13mm)	0.010" (0.25mm)	0.020" (0.51mm)
-----------------	-----------------	----------------	-----------------	-----------------	-----------------

LAST REVISED: 06/06/2022

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.

EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DESCRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER'S LITERATURE ARE TYPICAL PROPERTIES ONLY.