

**TECHNICAL DATA SHEET****Flexible****1501****DESCRIPTION/ APPLICATION**

1501 is a flexible extrusion PVC compound formulated for exceptional clarity in USP Class VI applications. The compound possesses excellent color retention in applications requiring gamma radiation sterilization.

GENERAL PROPERTIES	VALUE	METHOD
Specific Gravity (+/- 0.02)	1.16	ASTM D-792
Hardness Delayed 10 sec, Shore A (+/- 3)	50	ASTM D-2240
MECHANICAL PROPERTIES	VALUE	METHOD
Tensile Strength, psi	1200	ASTM D-638
Elongation, %	450	ASTM D-638
100% Modulus, psi	400	ASTM D-638
RECOMMENDED STOCK TEMPERATURE		330°F

Revision Date: 10/19/2015

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.