



TECHNICAL DATA SHEET

Flexible

1651

DESCRIPTION/ APPLICATION

1651 is a flexible extrusion PVC compound formulated for exceptional clarity in USP Class VI applications. The compound possesses excellent color retention in applications requiring gamma radiation sterilization.

GENERAL PROPERTIES	VALUE	METHOD
Specific Gravity (+/- 0.02)	1.20	ASTM D-792
Hardness Delayed 10 sec, Shore A (+/- 3)	66	ASTM D-2240
MECHANICAL PROPERTIES	VALUE	METHOD
Tensile Strength, psi	2250	ASTM D-638
Elongation, %	410	ASTM D-638
100% Modulus, psi	850	ASTM D-638
Melt Flow (g/10 min) @ 175°C and 14910g	84.26	ASTM D-1238
RECOMMENDED STOCK TEMPERATURE		335°F

Revision Date: 10/19/2015

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.