

5/25/23, 11:00 AM

Salesforce



1702

Download as PDF



VINYL COMPOUNDS

1702 Flexible

PRODUCT DESCRIPTION		
This flexible compound is formulated to provide excellent clarity for a variety of healthcare and packaging applications that require CFR 21, NSF 51, and USP Class VI certifications.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.20	ASTM D-792
Hardness Delayed, Shore A (+/- 3)	70	ASTM D-2240
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Strength, psi	1800	ASTM D-638
Tensile Strength, MPa	12	ASTM D-638
Elongation, %	300	ASTM D-638
100% Modulus, psi	800	ASTM D-638
100% Modulus, MPa	6	ASTM D-638
ADDITIONAL INFORMATION	TYPICAL VALUE	TEST METHOD
Recommended Stock Temperature, °F	345	
REGULATORY LISTINGS AND CERTIFICATIONS		
FDA CFR21		
USP Class VI		
NSF 51		

Revised Date:01/29/2020

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.