

5/25/23, 12:32 PM

Salesforce



2152

Download as PDF



VINYL COMPOUNDS

2152
Flexible

PRODUCT DESCRIPTION		
This flexible, non-phthalate compound is formulated for a variety of building wire applications.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.35	ASTM D-792
Hardness Delayed, Shore A (+/- 3)	93	ASTM D-2240
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Strength, psi	3400	ASTM D-638
Tensile Strength, MPa	23	ASTM D-638
Elongation, %	250	ASTM D-638
100% Modulus, psi	2200	ASTM D-638
100% Modulus, MPa	15	ASTM D-638
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:04/08/2021

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.