

5/25/23, 12:36 PM

Salesforce



22930

Download as PDF



VINYL COMPOUNDS

22930 Flexible

PRODUCT DESCRIPTION		
This flexible compound is formulated for a variety of building wire, tray cable, and jacketing applications. This compound can service temperatures up to 75°C and is commonly used in riser and telecommunication applications with flame-retardant PVC primaries.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.41	ASTM D-792
Hardness Delayed, Shore A (+/- 3)	93	ASTM D-2240
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Strength, psi	2750	ASTM D-638
Tensile Strength, MPa	19	ASTM D-638
Elongation, %	300	ASTM D-638
100% Modulus, psi	2000	ASTM D-638
100% Modulus, MPa	14	ASTM D-638
THERMAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Low-Temperature Brittle Point, °C	-28	ASTM D-746
FLAMMABILITY PROPERTIES	TYPICAL VALUE	TEST METHOD
Limited Oxygen Index, %	32.5	
ADDITIONAL INFORMATION	TYPICAL VALUE	TEST METHOD
Recommended Stock Temperature, °F	370-380	
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:10/29/2019

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.