

5/25/23, 2:19 PM

Salesforce



2512

Download as PDF



VINYL COMPOUNDS

2512
Rigid

PRODUCT DESCRIPTION		
This rigid, non-phthalate compound is formulated for a variety of interior profile extrusion applications. This sustainable compound is partially formulated with recycled product to allow for a more cost-effective end product.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.44	ASTM D-792
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Yield Strength, psi	6500	ASTM D-638
Tensile Yield Strength, MPa	45	ASTM D-638
Tensile Modulus, psi	475000	ASTM D-638
Tensile Modulus, MPa	3275	ASTM D-638
Tensile Impact, ft-lbs/in ²	45.5	ASTM D-1822
Elongation, %	2.6	ASTM D-638
1/8" Notched Izod Impact ft-lbs/in at 23°C	3	ASTM D-256
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:04/08/2021

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.