

5/25/23, 12:38 PM

Salesforce



28850

Download as PDF



VINYL COMPOUNDS

28850 Flexible

PRODUCT DESCRIPTION		
This flexible, non-phthalate compound is formulated to provide excellent UV and oil resistance for a variety of tray cable and building wire applications. This soft compound can service temperatures up to 105°C and is commonly used in tray cable applications over FR inners.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.36	ASTM D-792
Hardness Delayed, Shore A (+/- 3)	85	ASTM D-2240
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Strength, psi	2400	ASTM D-638
Tensile Strength, MPa	17	ASTM D-638
Elongation, %	330	ASTM D-638
100% Modulus, psi	1500	ASTM D-638
100% Modulus, MPa	10	ASTM D-638
THERMAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Low-Temperature Brittle Point, °C	-26	ASTM D-746
FLAMMABILITY PROPERTIES	TYPICAL VALUE	TEST METHOD
Limited Oxygen Index, %	29.5	
ADDITIONAL INFORMATION	TYPICAL VALUE	TEST METHOD
Recommended Melt Temperature, °F	365	
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:10/29/2019

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.