



TECHNICAL DATA SHEET

Rigid

3265

DESCRIPTION/ APPLICATION

3265 is a special purpose rigid extrusion grade of PVC compound designed for applications requiring toughness, stability, ease of processing, durability, chemical resistance, and weathering properties in all colors.

MECHANICAL PROPERTIES	VALUE	METHOD
Specific Gravity	1.37	ASTM D-792
Tensile Strength, psi	6,800	ASTM D-638
Tensile Modulus, psi	339,000	ASTM D-638
Drop Dart Impact, in-lb/mil	1.6	ASTM D-4226, A
Drop Dart Impact, in-lb/mil	3.6	ASTM D-4226, B
1/8" Notched Izod Impact	2.58 ft-lbs/in @ 23°C	ASTM D-256
OTHER PROPERTIES	VALUE	METHOD
Heat Deflection Temperature, °C	74 @ 264 psi	ASTM D-648

Revision Date: 01/05/2016

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.