

5/26/23, 8:43 AM

Salesforce



3310

Download as PDF



VINYL COMPOUNDS

3310 Rigid

PRODUCT DESCRIPTION		
This rigid, non-phthalate compound is formulated for a variety of profile extrusion and building applications. This powder blend compound is available in weatherable colors.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.45	ASTM D-792
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Yield Strength, psi	6400	ASTM D-638
Tensile Yield Strength, MPa	44	ASTM D-638
Tensile Modulus, psi	480000	ASTM D-638
Tensile Modulus, MPa	3310	ASTM D-638
1/8" Notched Izod Impact ft-lbs/in at 23°C	17.1	ASTM D-256
THERMAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Heat Deflection Temp °C at 264 psi/1.8 MPa	68	ASTM D-648
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:10/29/2019

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.