

5/25/23, 12:54 PM

Salesforce



7540

Download as PDF



VINYL COMPOUNDS

7540 Flexible

PRODUCT DESCRIPTION		
This flexible compound is formulated to provide excellent UV resistance and low-temperature properties for a variety of exterior high-quality applications.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.15	ASTM D-792
Hardness Delayed, Shore A (+/- 3)	54	ASTM D-2240
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Strength, psi	1300	ASTM D-638
Tensile Strength, MPa	9	ASTM D-638
Elongation, %	500	ASTM D-638
100% Modulus, psi	415	ASTM D-638
100% Modulus, MPa	3	ASTM D-638
THERMAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Low-Temperature Brittle Point, °C	-50	ASTM D-746
ADDITIONAL INFORMATION	TYPICAL VALUE	TEST METHOD
Recommended Stock Temperature, °F	300	
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:10/29/2019

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.