



TECHNICAL DATA SHEET

Flexible

8897

DESCRIPTION/ APPLICATION

8897 is a general purpose flexible extrusion PVC compound formulated for increased impact performance and microbial resistance in demanding marine and boat bumper applications.

GENERAL PROPERTIES	VALUE	METHOD
Specific Gravity (+/- 0.02)	1.27	ASTM D-792
Hardness Delayed 10 sec, Shore A (+/- 3)	89	ASTM D-2240
Hardness Delayed 10 sec, Shore D (+/- 3)	37	ASTM D-2240
MECHANICAL PROPERTIES	VALUE	METHOD
Tensile Strength, psi	2680	ASTM D-638
Elongation, %	230	ASTM D-638
100% Modulus, psi	1880	ASTM D-638
Low Temperature Brittle Point, °C	-40	ASTM D-746
RECOMMENDED STOCK TEMPERATURE		355°F

Revision Date: 10/06/2015

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.