



TECHNICAL DATA SHEET

Rigid

9109J

DESCRIPTION/ APPLICATION

9109J is a rigid extrusion PVC compound for interior applications. This compound contains an ultraviolet stabilizer, which retards severe color change and is designed for use in price tag holders.

GENERAL PROPERTIES	VALUE	METHOD
Specific Gravity (+/- 0.02)	1.34	ASTM D-792
Hardness Delayed 10 sec, Shore D (+/-3)	75	ASTM D-2240
MECHANICAL PROPERTIES	VALUE	METHOD
Tensile Yield Strength, psi	6,700	ASTM D-638
Tensile Modulus, psi	360,000	ASTM D-638
Flexural Strength, psi	12,000	ASTM D-790
Flexural Modulus, psi	350,000	ASTM D-790
1/8" Notched Izod Impact	10.0 ft-lbs/in @ 23°C	ASTM D-256

Revision Date: 9/29/2015

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.