

Georgia Gulf

Data Sheet

9129J Clear

Georgia Gulf 9129J Clear is designed for use in extruded price tag holders. The compound contains an ultraviolet light stabilizer which retards color change.

General Properties	Test Method	Typical Value
Specific Gravity	ASTM D-792	1.35
Mechanical Properties	Test Method	Typical Value
Tensile Yield, psi	ASTM D-638	6,800
Tensile Modulus, psi	ASTM D-638	360,000
Flexural Strength, psi	ASTM D-790	11,900
Flexural Modulus, psi	ASTM D-790	350,000
Hardness, Shore D	ASTM D-2240	75
$\frac{1}{8}$ " Notched Izod Impact, ft-lbs/in (23°C)	ASTM D-256	1.9
$\frac{1}{8}$ " Notched Izod Impact, ft-lbs/in (0°C)	ASTM D-256	1.6

1D

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. These values and sets of properties are based upon laboratory work with small scale equipment and do not necessarily indicate end product performance. Full scale testing and end product use and performance are the responsibility of the Buyer. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.
Typical Value may not be construed as product specifications.