

5/25/23, 1:53 PM

Salesforce



FG-9229

Download as PDF



VINYL COMPOUNDS

FG-9229 Rigid

PRODUCT DESCRIPTION		
This rigid, non-phthalate compound is formulated to provide excellent clarity and ease of processing for a variety of packaging and bottle applications that can either be blow molded or extruded. This food-grade compound is commonly used in food contact, cosmetic packaging, and general purpose applications.		
GENERAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Specific Gravity (+/- 0.02)	1.32	ASTM D-792
Cell Classification	16343	ASTM D-1784
MECHANICAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Tensile Yield Strength, psi	6300	ASTM D-638
Tensile Yield Strength, MPa	43	ASTM D-638
Tensile Modulus, psi	390000	ASTM D-638
Tensile Modulus, MPa	2689	ASTM D-638
Tensile Impact, ft-lbs/in ²	88	ASTM D-1822
Flexural Strength, psi	11500	ASTM D-790
Flexural Strength, MPa	79	ASTM D-790
1/8" Notched Izod Impact ft-lbs/in at 23°C	18	ASTM D-256
THERMAL PROPERTIES	TYPICAL VALUE	TEST METHOD
Heat Deflection Temp °C at 264 psi/1.8 MPa	60	ASTM D-648
OTHER PROPERTIES	TYPICAL VALUE	TEST METHOD
Transmittance, 1/8" pressed plaque, %	80	ASTM D-1003-61
Haze, 1/8" pressed plaque, %	5	ASTM D-1003-61
REGULATORY LISTINGS AND CERTIFICATIONS		
RoHS		

Revised Date:10/29/2019

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.