

KOREA PETROCHEMICAL IND.,CO.,LTD

HDPE **P601 HUBL**
 print
 close

Classification : HDPE Steel Pipe Coating grade
 Attributes : Abrasion Resistance, Weatherability, UV Stability, Color:Black
 Applications : Steel Pipe Coating

Documents & Certificates

Spec Sheet :  [kpic_spec_P601_HUBL_en.pdf](#)
 MSDS :  [kpic_msds_P601_HUBL_en\(1\).pdf](#)
 FDA :  [FDA Request](#)

Properties

ITEM (TERM)	VALUE	UNIT	TEST METHOD
Melt Index	0.3	g/10min.	ASTM D1238
Density	0.954	g/cm ³	ASTM D1505
Tensile Strength at Yield	210	kgf/cm ²	ASTM D638
Elongation at Break	>600	%	ASTM D638
Flexural Modulus	7,700	kgf/cm ²	ASTM D790
Hardness	62	Shore	ASTM D2240D
Impact Strength (Izod width Notch)	>50	kgf cm/cm	ASTM D256
Environment Stress Cracking Resistance	>5,000	hr.Cond.B.100%	ASTM D1693
Melting Point	132	°C	ASTM D3418
Softening Point (Vicat)	122	°C	ASTM D1525
Heat Deflection Temperature	58	°C	ASTM D648
Brittleness Temperature	< -70	°C	ASTM D746
Carbon Black Content	2.3	%	ISO 6964
Carbon Black Dispersion	<3	Grade	ISO 18553

The values given above should only be used as a guide and should not be considered as a specification or guarantee.

The values are dependent on part geometry and fabrication conditions.